

Greenlots Product Overview

Item	Description
Enclosure	Robust high-impact ABS enclosure
	Aluminium/ galvanised mild steel/ stainless steel
Number of socket(s)	
Control pilot	CP-Communications box 16A or 32A 230V/50Hz, Mode 3 according to IEC 61851
Electric shock protection circuit breaker	Internal earth leakage protection (RCD) sensitivity 30mA
Smart energy meter	MID- certified; accuracy according to IEC 61036 for class 1 or 2; with communications module
Authentication	RFID authorization technology
Voltage and currents	230V/400V, 16A/32A
Customizable message display	Send personalized messages to the user via charger display
LCD display	Ultrabright TFT-LCD display
Communications	Real-time communication via GSM/GPRS for status updates and remote control
Mounting	
Availability	
Applications	



Smart Grid Enabled

Greenlots Home	Greenlots Point	Greenlots Avenue
✓	✓	
		✓
1	1	2
✓	✓	✓
✓	✓	✓
	✓ (with remote communications)	
	✓	
✓	✓	✓
	✓	
	✓	
Wall-mounted	Wall-mounted	Ground-mounted
Immediate	Immediate	Immediate
Private charger (e.g., Outdoor Garage)	Semi-Public charger (e.g., Shopping Centers)	Semi-Public charger (e.g., Roadside)